



1114

WOCADIRECT
(877) 962 2645 info@wocadirect.com

WOCA ACTIVE STAIN INSTRUCTIONS

WOCA Active Stain is water based and was developed to produce unique aged grey effects in white oak/European oak. The product is non-corrosive. Active Stain reacts with tannic acid in the oak. Color may vary depending on the amount of tannin in the wood.

Work Instructions:

1. The wood must be clean, dry and free from dirt and grease. We recommend application as soon as possible after sanding.
2. Shake container, especially #2 and #4, and pour into a paint tray. Stir regularly during application.
3. Apply an even coat of Active Stain with a brush, paint roller or synthetic applicator, following the wood grain.
4. Apply at least one liter of Active Stain for every 100 sq.ft. of floor or woodwork.
5. On vertical wood surfaces, apply from top to bottom.
6. Let floor or woodwork dry at least 2 hours.
7. Wash floor with WOCA Wood Cleaner, as this will neutralize tannins and prevent water spotting (see Wood Cleaner instructions.) Let the floor dry completely, preferably overnight!
8. De-nib standing fibers with a fine abrasive polishing pad or thick green pad under a standard buffer until floor is smooth and vacuum the floor before final treatment.
9. Finish the floor or woodwork with WOCA oil.

Please Note: Oak treated with Active Stain tends to darken when subjected to both direct and indirect sunlight. To minimize this effect, Active Stain may be diluted with water prior to application.

Packaging: 2.5 liter containers

Coverage: 250 s.f.

Quick link to Woca application videos: <http://shop.wocadenmark.com/we-are-here-to-help/how-to-do/>