

WOCA Maintenance Paste

Maintenance Paste is used for the refreshing and maintenance of oiled wood floors and also is especially suitable for UV-oiled floors.

Maintenance Paste is available in 14 oz. tubes in the colors natural and white.

Consumption:

Initial Site Finish - 325 to 350 sq. ft. per tube.

Maintenance - 750 to 1,200 sq. ft. per tube.

Tools

Buffer, White buffer pads, and Cotton cloths.

Please notice!

Risk of self-ignition! Due to the risk of self-ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use.



How to do...

Before a new oiled floor is used, it is recommended to buff it with a coat of Maintenance Paste. The application gives a hard-wearing surface. Oiled floors should be maintained periodically depending on wear. Floors that are exposed to extremely hard wear should be maintained often.

1 Clean the floor with a solution of 1/4 cup Wood Cleaner per gallon of water. Leave the floor to thoroughly dry. The floor must be completely dry before the paste application.

2 Buff a thin coat of Maintenance Paste onto 100 s.f. of the floor at a time with white polishing pad.

3 Make sure that the Maintenance Paste is polished uniformly into the wood. Buffing continues until the wood appears saturated and silk-mat. Apply more paste if necessary. Polish again with cloths under a white pad to remove any excess paste.

4 If a more lustrous finish is desired, polish the area again with a white pad. Continue until the whole floor is coated. Let the surface rest for 6 hours before allowing foot traffic. Do not expose the floor to water for 48 hours after finishing.

